

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 24 978 - 05 HH

Company Göpfert AG
Industriestraße
25795 Weddingstedt, GERMANY

Product Description Quick Closing Valve

Type Straight Type No. 26.01.01
Angle Type No. 26.01.02

Environmental Category None

Technical Data / Range of Application **TECHNICAL DATA:**
Materials:
Body / Valve cover EN-GJS-400-18-LT, GS-C25, G-CUSn5ZnPb
Spindle, Disc, Seat X14CrMoS17, X12Cr13, G-CUSn5ZnPb
Spindle sealing FKM / FPM / Graphite
Actuator Pneumatic, Hydraulic
Size range DN 15 - DN 125 / DN 150 - DN 200
Nominal pressure PN 16 / PN 10
Temperature range 0°C up to 150°C (acc. to sealing material of spindle)

RANGE OF APPLICATION:

The quick closing valves of type 26.01.01 and 26.01.02 are type approved for the use on storage tanks and in piping systems according to the Rules I-1-2 - Machinery Installations, Section 11.

Test Standard VI-7-8 Test Requirements for Components and Systems of Mechanical Engineering : 2008

Documents - Test report no.: 573-05 issued by Pac Consult , Vibration test
- Drawings: 26.01.01.04-10A/26.01.01.12-18A/26.01.22-29A/26.01.02.04-10A/26.01.02.12-18A/26.01.02.22-29A

Remarks Valves included in pipe class II are subject to final inspection by a GL surveyor.

Valid until 2015-03-16

Page 1 of 1

Type Approval Symbol



File No. II.A.16

Hamburg, 2010-03-12

Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Hagen Markus
Hagen Markus