



Germanischer Lloyd

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 24 978 - 05 HH

Company Göpfert AG
Industriestraße
25795 Weddingstedt

Product Description Quick Closing Valve

Type Straight type no. 26.01.01
Angle type no 26.01.02

Environmental Category None

Technical Data /
Range of Application TECHNICAL DATA:
Materials:
Body / Valve cover EN-GJS-400-18-LT (GGG 40.3) or G-CUSn5ZnPb
Spindle, Disc, Seat X20Cr13 or G-CUSn5ZnPb
Spindle sealing FKM / FPM
Actuator Pneumatic, Hydraulik
Size range DN 15 - DN 125 / DN 150 - DN 200
Nominal pressure PN 16 / PN 10
Temperature range 0°C up to 150°C (acc. to sealing material of spindle)

RANGE OF APPLICATION:

The quick closing valves of type 26.01.01 and 26.01.02 are type approved for the use on storage tanks and in piping systems according to the Rules of Germanischer Lloyd, Chapter 2, Machinery Installations, Sec.11.

Test Standard Regulations for the Performance of Type Tests, Part 6 - Test Requirements for Mechanical Components and Equipment, Edition 1998

Documents - Test report no.: 573-05 issued by Pac Consult , Vibration test
- Drawings: 26.01.01.04-10A/26.01.01.12-18A/26.01.22-29A/26.01.02.04-10A/26.01.02.12-18A/26.01.02.22-29A

Remarks Valves included in pipe class II are subject to final inspection by a GL surveyor.

Valid until 2010-03-16

Page 1 of 1

Type Approval Symbol



File No. II.A.16

Hamburg, 2005-03-17

Germanischer Lloyd

G. Hölzer
G. Hölzer

H. Markus
H. Markus